

## Water Treatment Systems



PURA is an advanced Ultraviolet Water Treatment System. It had been designed with you, the consumer, in mind. PURA Products are lightweight, easy to use and simple to maintain. PURA Products will provide you with clean, disinfected drinking water for years to come.



### All PURA Products feature:

- Water disinfection
- Easy to change lamp and filters
- Lamp and ballast matched for quality assurance
- Simple installation

These systems are for the supplemental treatment of disinfected drinking water which has been treated or other drinking water which has been tested and deemed acceptable for human consumption by the state or local health agency having jurisdiction. These systems are designed to reduce normally occurring non-pathogenic nuisance organisms and is not intended for the treatment of contaminated water. The contaminants and other substances reduced by this water treatment device are not necessarily in your water. In addition, the presence of certain contaminants in your drinking water does not necessarily pose a health risk.

## UV1-EPCB Series™

PURA Product's UV1-EPCB Series is a bright example of PURA's patented All-In-One concept. This product combines both ultraviolet disinfection with carbon filtration all in a very attractive and compact system. The UV1-EPCB Series is rated for 1 gallon per minute and uses either a 0.5 micron (EPCB) carbon block filter or a 10 micron (EPCB 10) carbon block filter (optional). This easy to install system can be used as a stand alone or in conjunction with other water treatment products.



### Features:

- Compact size
- Standard voltage 115V

### Options:

- 220V / 50 Hz (2-prong Euro plug)
- 12V DC

## Specifications & Performance UV1-EPCB Series

Item #	Model Description	# of Sumps	Sump Type	Sump Content	Lamp #	Power Used	Flow Rates <sup>1</sup> GPM (L/min)	Dimensions In. (cm) H x W x D	Shipping Weight Lbs. (Kg)	Inlet/Outlet Size
15910111	UV1-EPCB	1	#10SL	EPCB Carbon/UV	#10	10 Watts	1 (3.8)	13.5 x 5.0 x 5.0 Carbon/UV	7.0 (3.2)	1/2" NPT

**NOTE:** <sup>1</sup> All flow rates shown will provide a UV dose of no less than 16,000 mW-s/cm<sup>2</sup> or greater; EPCB refers to Extended Pass Carbon Block Filter.

## UV20 Series™

PURA Product's UV20 Series is designed to provide disinfected water at a flow rate of 8 - 10 gallons per minute. This system is ideal for whole house water treatment. In addition to disinfection, the double and triple models provide filtration for the removal of sediment and chemical contaminants. This ultraviolet water treatment system makes a perfect companion to water softeners, distillers, reverse osmosis and ozone systems. The UV20 Series has proven to be PURA's most popular product line and has created an industry standard in whole-house disinfection.



### Features:

- Electronic lamp indicator (LED)
- Standard voltage 115V

### Options:

- 220V / 50 Hz (2-prong Euro plug)
- 12V DC
- Lamp Out Circuit (LOC) - (normally open) Safety monitor for alarm
- Lamp Out Circuit (LOC) - (normally closed) Safety monitor for solenoid shut off

## Specifications & Performance UV20 Series

Item Number	Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Lamp #	Power Used	Flow Rates¹ GPM (L/min)	Dimensions In. (cm) H x W x D	Shipping Weight Lbs. (Kg)	Inlet/Outlet Outlet
15710100	UV20-1	1	#20	UV	none	none	#20	22 Watts	10 (38)	25 x 5.5 x 5.5 (63.5 x 14 x 14)	16.0 (7.3)	3/4" NPT
15710400	Normally Closed											
15710500	Normally Open											
15720121	UV20-2 SD	2		5 Micron Sed Filter	UV	none			10 (38)	25 x 11 x 5.5 (63.5 x 27.9 x 14)	23.0 (10.4)	
15720421	Normally Closed											
15720521	Normally Open											
15730131	UV20-3 SD/CB	3		5 Micron Sed Filter	10 Micron Carbon Block	UV			8 (30)	25 x 16 x 5.5 (63.5 x 40 x 14)	33.0 (15.0)	
15730431	Normally Closed											
15730531	Normally Open											

**NOTE:** <sup>1</sup> All flow rates shown will provide a UV dose of no less than 16,000 mW-s/cm<sup>2</sup> or greater.

## UVB Series™

PURA Product's patented UVB Series is designed to provide disinfected water at a flow rate of 2 gallons per minute. In addition to disinfection, water is filtered through our 0.5 micron Extended Pass Carbon Block (EPCB) filter.

Our double and triple models provide you with additional filtration with sediment and activated carbon filters.

This compact All-in-One system installs with ease and can be used anywhere that clean, clear, good tasting disinfected water is needed. It is ideal for point-of-use applications like: under the kitchen sink, office water coolers, water vending machines, boats, recreational vehicles, etc.



### Features:

- Electronic lamp indicator (LED)
- Standard voltage 115V

### Options:

- 220V / 50 Hz (2-prong Euro plug)
- 12V DC
- Lamp Out Circuit (LOC) - (normally open) Safety monitor for alarm
- Lamp Out Circuit (LOC) - (normally closed) Safety monitor for solenoid shut off

## Specifications & Performance UVB Series

Item #	Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Lamp #	Power Used	Flow Rates <sup>1</sup> GPM (L/min)	Dimensions In. (cm) H x W x D	Shipping Weight Lbs. (Kg)	Inlet/Outlet Size
15610111	UVB1-EPCB	1	#10	EPCB Carbon/UV	none	none	#11	14 Watts	2 (7.6)	15 x 5.5 x 5.5 (38.1 x 14 x 14)	10.0 (4.5)	3/8" NPT
15610411	UVB1-EPCB Normally Closed											
15610511	UVB1-EPCB Normally Open											
15620121	UVB2-EPCB/SD	2	#10	5 Micron Sed Filter	EPCB Carbon/UV	none	#11	14 Watts	2 (7.6)	15 x 11 x 5.5 (38.1 x 27.9 x 14)	15.0 (6.8)	
15630131	UVB3- EPCB/GC/SD	3			Granular Carbon Filter	EPCB Carbon/UV				15 x 16 x 5.5 (38.1 x 40.6 x 14)	24.0 (10.9)	

**NOTE:** <sup>1</sup> All flow rates shown will provide a UV dose of no less than 16,000 mW-s/cm<sup>2</sup> or greater.

## UV Addon Series™

PURA Product's UV ADDON Series is designed to be an easy addition to water treatment systems that require ultraviolet disinfection (RO systems, holding tanks, water dispensers, recirculating systems and more). The ADDON systems are available with a 1 GPM or 3 GPM flow rate. They are constructed using a 304 grade stainless steel body with a molded head that includes 3/8" quick connect fittings on the inlet/outlet. This versatile system also includes a heavy duty mounting bracket, but will also fit standard 2" RO mounting clips. The UV Addon Series can be used almost anywhere and is equipped with a unique power supply that makes installation simple, space requirements minimal and lamp changes easy.



### Features:

- Standard voltage 115V
- 3/8" quick connect fittings

### Options:

- 220V / 50 Hz (2-prong Euro plug)
- 12V DC

## Specifications & Performance UV Addon Series

Item #	Model Description	# of sumps	Sump Type	Sump Content	Lamp #	Power Used	Flow Rates <sup>1</sup> GPM (L/min)	Dimensions In. (cm) H x W x D	Shipping Weight Lbs. (Kg)	Inlet/Outlet Size
15510100	UV Addon-1	1	304 SS	UV	#10	10 Watts	1 (3.8)	12 x 4 x 3.5 (30.5 x 10 x 8.9)	5.0 (2.3)	3/8" QC
15530100	UV Addon-3				#20	22 Watts	3 (11.4)	22.5 x 4 x 3.5 (57 x 10 x 8.9)	7.0 (3.2)	

**NOTE:** <sup>1</sup> All flow rates shown will provide a UV dose of no less than 16,000 mW-s/cm<sup>2</sup> or greater.

## UV BigBoy Series™

The UV BigBoy Series is the most versatile commercial ultraviolet disinfection system on the market today. This 15 to 60 GPM series is manufactured with versatility in mind, and is virtually unlimited in the possible filter configurations and manifold sequences. The series is designed with the same traditional style that PURA has made an industry standard - worldwide.

The UV BigBoy Series, with its capacity, versatility and cost, is the world's most flexible, complete water disinfection system in its class.



### Features:

- Electronic lamp indicator (LED)
- Standard voltage 115V

### Options:

- 220V / 50 Hz (2-prong Euro plug)
- 12V DC
- Lamp Out Circuit (LOC) - (normally open) Safety monitor for alarm
- Lamp Out Circuit (LOC) - (normally closed) Safety monitor for solenoid shut off

## Specifications & Performance UV BigBoy Series

Item #	Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Lamp #	Power Used	Flow Rates¹ GPM (L/min)	Dimensions In. (cm) H x W x D	Shipping Wgt. Lbs. (Kg)	Inlet/Outlet Size		
15810100	UVBB-1	1	#20BB	UV	none	none	#20	22 Watts	15 (57)	28 x 7.5 x 9.0 (71.1 x 19 x 22.9)	18.0 (8.2)	1-1/2" NPT		
15810400	UVBB-1 Normally Closed													
15810500	UVBB-1 Normally Open													
15820121	UVBB-2	2		5 Micron Sed Filter	UV	none				28 x 15 x 9.0 (71.1 x 38.1 x 22.9)	35.0 (15.9)			
15820421	UVBB-2 Normally Closed													
15820521	UVBB-2 Normally Open													
15830131	UVBB-3	3		5 Micron Sed Filter	10 Micron Carbon Block	UV							28 x 23 x 9.0 (71.1 x 58.4 x 22.9)	54.0 (24.5)
15830431	UVBB-3 Normally Closed													
15830531	UVBB-3 Normally Open													

**NOTES:** <sup>1</sup>All flow rates shown will provide a UV dose of no less than 16,000 mW-s/cm<sup>2</sup> or greater.

## Conditions For Use - All PURA UV Models

Source Water Supply Profile		Chemical Parameters	Max mg/L
Feed Water Pressure†	20 – 75psig (138 – 517kPa)	Hardness (CaCO <sub>3</sub> )	< 120 (7 GPG)
Feed Water Temperature	38° – 105°F (3.3° – 40.5°C)	Iron (Fe)	< 0.3
pH Range	6.5 – 9.5	Manganese (Mn)	< 0.05
Total Dissolved Solids	< 1500 mg/L	† Water Pressure must not exceed 75 psig (517 kPa) or a pressure regulator must be installed.	
Total Suspended Solids	< 10 mg/L		
Turbidity	< 5 NTU		

U.S. Patent #4,971,687



### WaterGroup Inc.

#### U.S. Headquarters

193 Osborne Road, Fridley, MN 55432

TOLL FREE PHONE: 877-581-1833

TOLL FREE FAX: 800-544-6651

EMAIL: customerserviceusa@watergroup.com

#### Distribution Facilities:

Durham, NC / Libertyville, IL / Pottstown, PA

Rancho Cucamonga, CA / San Antonio, TX / Tampa, FL

### WaterGroup Companies, Inc.

#### Canada Headquarters

490 Pinebush Road, Unit 1, Cambridge, ON N1T 0A5

TOLL FREE PHONE: 877-288-9888

TOLL FREE FAX: 800-223-8296

EMAIL: customerservicecanada@watergroup.com

#### Distribution Facilities:

Cambridge, ON / Calgary, AB

[www.watergroup.com](http://www.watergroup.com)

57017.0913

#### AUTHORIZED DEALER INFORMATION



De los perales N47-108 y Av. Eloy Alfaro, Quito.

Telefono: 02-2449 158

ventas@idimafiltros.net

