

er

Eliminate Diesel Fuel Contamination Problems

- · Significant flow restriction prevents harmful amounts of water from passing downstream
- Removes silt and rust
- Effective protection combined with economical life

DESCRIPTION

AD Series Aquacon[®] cartridges were developed in cooperation with a majo oil company for diesel fuel applications. Balancing effective water and dirt removal with economical life, AD cartridges have become standard for most diesel users and can also be used with biodiesel.

Nominal filtration efficiency is 25 microns. Effluent water levels are typically below 50 parts per million. The AD design significantly restricts flow when a water slug is introduced.

Motor gasoline, hydraulic and lube oils can also be filtered with AD cartridges. Aviation fuels, however, must be filtered with the more efficient series design

APPLICATIONS

- Diesel Fuel
- **Biodiesel Blends** •
- FAME

CARTRIDGE INFORMATION

Model Number	Dimensions (inches)	Max. Diesel Flow Rate per cartridge (GPM)	Use
AD-21025	2 ⁵ / ₈ x 9 ³ / ₄	15	Velcon VF-31E Housing
AD-51225	5 ⁵ /8 x 12 ¹ /4	50	Velcon VF-61 Housing
AD-52425	5 ⁵ /8 x 24 ¹ /2	100	Velcon VF-62 Housing
AD-60925	6 x 9 ¹³ / ₁₆	35	Velcon VF-609 /Facet VFCS-21 /Racor FBO-10 Housings
AD-61225	6 x 13 ^{11/} 16	46	Facet VFCS-22 /Racor FBO-14 Housings
AD-61425	6 x 14 ¹ /2	50	Velcon Aviation Housings
AD-71825	6¹/₄ x 18	60	Velcon Industrial Housings

WARNING: Absorbent-type monitor cartridges will not remove water from fuel containing alcohol-blending agents (commonly called gasohol). For removal of solids, please use Velcon particle removal filters specifically made for gasohol. Consult your Velcon representative.

© 2011 Velcon Filters, LLC.



Velcon products are sold and serviced by a world-wide representative network. To order, contact Headquarters or your LOCAL REPRESENTATIVE:

COMPANY HEADQUARTERS: Velcon Filters, LLC 1210 Garden of the Gods Road Colorado Springs, CO 80907-3410 Phone: 1.800.531.0180 / 1.719.531.5855 Fax: 719.531.5690 e-mail: vfsales@velcon.com www.velcon.com MANUFACTURING PLANTS LOCATED AT: Colorado Springs, Colorado Sylacauga, Alabama Henryetta, Oklahoma

1655-R7 08/11



Liquid Filtration and Separation Specialists

	acon® Filt Cartridg AD Ser		
at the Pump			

OFFICES AND AFFILIATES IN: Canada, Germany, Singapore, & Spain